



Body Fillers

# Easy Stop

# KENT



UPDATED: 19.03.09

A super smooth two component polyester stopper in a creamy, easy to mix and apply formula.

Part N°: 83330 1.1L Tin  
Part N°: 83331 1.3L Dispenser

## Features

- Can be over-painted with most paint systems
- Fast cure
- Uniform ultra fine smooth consistency
- High fill and non sag properties
- Excellent sandability

## Benefits

- Use with confidence
- Sandable 20-30 minutes at 20 C
- Can be applied with minimum mess or waste
- Can be used to fill large areas in one operation
- Will produce a professional finish

## Applications

Use to fill small dents and imperfections on all metal surfaces and rigid plastics.

Easy stop filler can be used on the following surfaces:-

- Bare steel – degrease and abrade with P40 paper.
- Polyester body filler - degrease and abrade with P80 paper.
- Original paint surfaces (with the exception of thermoplastic acrylics) - degrease and abrade with P180 paper.

## Instructions

• The surface to be treated must be de-rusted, degreased, dry, dust-free and slightly roughened. All prior coats both unhardened lacquers and thermo-plastic acrylic varnishes must be removed.

- Add 2 parts of red hardener paste to 98 parts of filler.
- Both components are mixed until a homo-geneous shade of colour is achieved. The mixture has a pot-life of about 4 to 5 minutes.
- After 20 to 30 minutes the hardened filler will be sandable
- The hardening process is accelerated by heat and delayed by cold
- The filled surface can be worked over with all fillers and lacquers available on the market.

- Always use a mixing pallet, this minimises inclusion of air and reduces risk of contamination from other products
- Panel wipes should always be used to remove surface contamination
- Use KENT spray guide to detect imperfections in final work.

DS275

## Hints & Tips

Excess hardener will not significantly speed up the gel time and could lead to bleed through and bleaching problems during over-painting



## Easy Stop

### Technical Information



Part number:	83330-83331	Specific gravity:	1.8g/ml
Description:	Easy stop	Mixing ratio:	98:2
Part code:	KEST/KESD	Work time:	4-5 mins
Shelf life:	12 mths from manufacturing	Sanding time:	20-30mins
Selling Unit:	Ea	Overcoating:	1 hour
Hazard Info:	Harmful and oxidising	Service temp:	-20 to + 120°C
Replacing:	n/a	Shore D:	70-80
VOC:	100 G/L	<b>Bond Strength:</b>	
Customs Tariff code:	321410100	Steel:	3500N
MSDS:	yes	Galvanised:	1500N
		Aluminium:	3000N

#### Associated Products :

Abrasives, Acrysol, Plastic Repair system (PRS), Quickfill, General filler range, Scuff Repair kit, Plastic prep, mixing pallet

#### VOC

#### Markings :



2004/42/IIB(b)(250)100

#### Market

#### Segments :

Abrasives, Acrysol, Plastic repair system (PRS), Quickfill (QFL), General Filler Range, Scuff Repair Kit (SCF), Plastic Prep, mixing pallet, Spray Guide

#### Health & Safety Information :



**HARMFUL**  
Contains styrene

##### PART 83332a (filler)

R10 FLAMMABLE.  
R20 Harmful by inhalation.  
R36/38 Irritating to eyes and skin.  
S3 Keep in a cool place.  
S46 If swallowed, seek medical advice immediately and show this container or label  
S51 Use only in well ventilated areas



**HARMFUL**  
Contains benzoyl peroxide

##### PART 83332b (hardener)

R7 May cause fire.  
R36 Irritating to eyes.  
S3/7 Keep container tightly closed in a cool place.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S46 If swallowed, seek medical advice immediately and show this container or label



**OXIDISING**

In order to provide you with the most appropriate Personal Protective Equipment when using our products, KENT advises that you follow the guidelines on the packaging of the product before use. The guidelines are there for your protection and KENT provides a range of Personal Protection Equipment such as clothing, eye glasses, goggles, face shields and breathing apparatus, complying with the latest European legislation. If you require further advice then please phone our freephone number and we will be pleased to help you. Telephone: 0800 136925

#### Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT UK.

This data sheet and its contents (the "Information") belong to KENT UK or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the business assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the business was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the business liability for death or personal injury resulting from its negligence.

**Registered Office:** 151 Longsight, Bolton, Lancashire BL2 3JE  
Registered in England N°: 02519917  
VAT Registration N°: 125 0226 61  
All rights reserved.

**KENT UK, Pitreavie Crescent, Pitreavie Business Park, Dunfermline, Fife KY11 8UQ**  
Tel : Freephone 0800 136925 or 01383 737393 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or  
Email: [KENTsales.UK@kenturope.com](mailto:KENTsales.UK@kenturope.com)

DS275