

Food Grade Grease +



UPDATED: 25.05.10



A high quality lubricant for use in applications where there is a risk of incidental contact with food.

Part N^o: **83691 - 400ml aerosol**

Features & Benefits

- Water resistant – Will not wash when exposed to water and steam
- A fully approved NSF grease which meets USDA 1998 H1 guidelines - Safe for use in areas with in-direct food contact
- Excellent capillary action - Easily penetrates areas with difficult access
- Temperature range -50°C to +165°C - Excellent long-term lubrication and rust protection
- Extended tube nozzle supplied - Can be applied with a high degree of accuracy to avoid overspray

Application

Food Grade Grease+ is suitable for all areas of lubrication in food and associated industries.

It gives extra wear protection with excellent high temperature and low friction properties.

Ideal for lubricating working mechanisms on agricultural equipment, mobile catering vehicles and commercial vehicles involved in the transport of foodstuffs.

Applications include: transmission mechanisms, chains, rollers, hoppers, bearings, rails, hinges and agricultural plant, for industry, fleet and individual operators of forklifts, mobile catering vehicles, refrigerated vehicles, farm machinery, animal transport vehicles, and produce transport vehicles.

Instructions

1. Shake well before use.
2. Remove old lubricants and any surface contamination.
3. Spray in a well ventilated area from a distance of 15-20cm. Allow to penetrate.
4. Use the extension tube for difficult to reach areas.
5. Re-apply as necessary.

DS349

Hints & Tips



Certificate No.1427/97

Certificate No.1427/97

Food Grade Grease +



Technical Information

Part N°:	83691	Appearance:	Ivory white smooth grease
Description:	Food Grade Grease + 400 ml	Water Resistance:	Excellent resistance
Shelf Life:	24 months	NLGI grade:	2
Selling Unit:	EA	Penetration worked:	265-295 units
VOC:	497g/l	Drop point:	>300°C
Tariff Code:	3409 99 10	USDA rating:	NSF – USDA H1
SDS:	Yes	Temp range;	-50°C to +165°C
Labels:	27	Density :	0.900g/ml
		Four ball test (welding):	480 - 500 kg
		Corrosion test (EMCOR):	0 – 0

Associated Products:

Food safe Foam Cleaner, Food safe Liquid cleaner, food solvent cleaner, Food safe silicone spray, Electric cleaner NSF, Food Grade KD400, Hi Tech food grease, (spray + bulk)

Market Segments



Health & Safety Information



IRRITANT

R38 Irritating to skin. R50/53 Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.



DANGEROUS FOR THE ENVIRONMENT

R67 Vapours may cause drowsiness and dizziness.

S16 Keep away from sources of ignition - No smoking.



EXTREMELY FLAMMABLE

S23 Do not breathe aerosol. S29 Do not empty into drains.

S51 Use only in well-ventilated areas.

In order to provide you with the most appropriate Personal Protective Equipment when using our products, KENT advises that you follow the guidelines on the packaging of the product before use. The guidelines are there for your protection and KENT provides a range of Personal Protection Equipment such as clothing, eye glasses, goggles, face shields and breathing apparatus, complying with the latest European legislation. If you require further advice then please phone our freephone number and we will be pleased to help you. Telephone: 0800 136925

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT UK.

This data sheet and its contents (the "Information") belong to KENT UK or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the business assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the business was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the business liability for death or personal injury resulting from its negligence.

Registered Office: 151 Longsight, Bolton, Lancashire BL2 3JE
Registered in England N°: 02519917
VAT Registration N°: 125 0226 61
All rights reserved.

KENT UK, Pitreavie Crescent, Pitreavie Business Park, Dunfermline, Fife KY11 8UQ
Tel : Freephone 0800 136925 or 01383 737393 between 08:30-17:30 Monday-Thursday,
09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or
Email: KENTsales.UK@kenteurope.com

DS349