

Ceramic 1200

A high temperature ceramic based grease containing boron nitride particles for added temperature resistance. Ceramic 1200 is ideal for the greasing nuts and bolts during disassembly. It has very good resistance to water and acids giving protection against rust / corrosion.



Part N^o: 85235 (C1200) - 400ml aerosol

Features

- Heavy metal free
- Very high temperature range -40°C to +1200°C
- Specified for ABS braking systems
- Assembly or dis-assembly grease
- Grey Colour
- Prevents oxidation

Benefits

- Safe to use
- Use on a wide variety of applications
- No comebacks
- Reduced inventory
- Less obvious in visible locations i.e. wheel nuts
- Easy to dis-assemble, saves time

Applications

“Ceramic grease is extremely well suited for use where copper based greases would normally be used i.e where there is a considerable amount of heat generated and/or water present. Application areas are on braking systems on the rear face of brake pads and on moving edges of brake shoes. It is also used to prevent items seizing or rusting together, particularly where they are regularly dismantled for service reasons i.e wheel stud threads and where Alloy road wheels seat onto Steel hubs. C1200 is also used for either freeing off, or assembling studs/nuts in areas where very hot temperatures are encountered such as exhaust systems. Finally, C1200 is ideal for preventing ABS sensors corroding into their housings.

Instructions

1. Shake well before use.
2. Apply directly onto the area to be lubricated.

Hints & Tips

DS24

0095 01



Certificate No. 1427/97

Certificate No. 1427/97

Ceramic 1200

Technical Information



Part N°:	85235	Consistency:	Medium / high viscosity grey grease
Description:	Ceramic grease, 400ml	Water Resistance:	Excellent water resistance
Shelf Life:	24 months	Heat Resistance:	1200°C
Selling Unit:	EA	Lubrication properties:	2600 N (DIN51350) (Four ball weld)
Hazard info:	Extremely Flammable	NLGI class:	1-2 (DIN 51818)
	Dangerous for the Environment	Dropping point:	>250 °C (DIN/ISO 2176)
VOC:	456g/l	Cone penetration (0.1 mm)	300-320 (DIN/SIO 2137)
Stock Code:	C1200	Corrosion protection:	0-0 (DIN 51802)
Customs Tariff Code:	3403 99 10	(Emcor Test)	
Pack=Each:	1	+3% NaCl	2-2
MSDS:	Yes	Copper corrosion:	1:100 (DIN 51811)
Replacing Product:	84055		

Associated Products: Brake Parts Cleaner 2 (BPC2), Pro Brake (KPB), Brake Silencer (BT72), K44 Silicone Grease

Market Segments:

Primary



Secondary



Health & Safety Information



Dangerous for the environment

R51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
S23 Do not breathe aerosol.



EXTREMELY FLAMMABLE

S46 If swallowed, seek medical advice immediately and show this container or label.

S51 Use only in well-ventilated areas.

WARNING: Pressurised container: protect from sunlight and do not heat to above 50°C. Do not pierce or burn even when empty. Do not spray on to naked flame or any other ignition source.

In order to provide you with the most appropriate Personal Protective Equipment when using our products, KENT advises that you follow the guidelines on the packaging of the product before use. The guidelines are there for your protection and KENT provides a range of Personal Protection Equipment such as clothing, eye glasses, goggles, face shields and breathing apparatus, complying with the latest European legislation. If you require further advice then please phone our freephone number and we will be pleased to help you. Telephone: 0800 136925

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of Barnes Group KENT Ltd.
This data sheet and its contents (the "Information") belong to the Barnes Group KENT Ltd or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the Group assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the Group was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the Group's liability for death or personal injury resulting from its negligence KENT is the trading name of Barnes Group KENT Ltd.

Registered Office:
36-48 Queen Street, Horsham, West Sussex RH13 5AD
Registered in England N°: 1164516
VAT Registration N°: 887 1228 94
All rights reserved.

KENT UK: 36 – 48 Queen Street, Horsham, West Sussex, RH13 5AD
Tel: +44 (0) 1403 213355 Fax: +44 (0) 1403 213343 www.kenturope.com
Barnes Group KENT Ltd 2006