

Black Filler



KENT Black Filler is a finely pigmented two-pack polyester black filler ideal for both large areas and SMART repairs



Part N°: 2.0kg Tin 85492 34

Features

- Can be over-painted with most paint systems
- Extra fine grain
- Does not clog the abrasive
- High fill and non sag properties
- Excellent sandability
- Black colour

Benefits

- Use with confidence
- Gives a “feathered” edge
- Saves on abrasive costs
- Can be used to fill large areas in one operation
- Will produce a professional finish
- Creates a guide coat effect for sanding

Applications

Use to fill small dents/holes and imperfections on steel and GRP.

Black filler can be used on the following surfaces:-

- Bare steel – degrease and abrade with P40 paper.
- Aluminium and galvanised steels - degrease and abrade with P80 paper.
- Original paint surfaces (with the exception of thermoplastic acrylics) - degrease and abrade with P180 paper.

Instructions

• The surface to be treated must be de-rusted, degreased, dry, dust-free and slightly roughened. All prior coats both unhardened lacquers and thermo-plastic acrylic varnishes must be removed.

• Add 2 parts of red hardener paste to 98 parts of filler.

• Both components are mixed until a homogeneous shade of colour is achieved.


The mixture has a pot-life of about 4 to 6 minutes.

• After 20 to 30 minutes the hardened filler will be sandable

• The hardening process is accelerated by heat and delayed by cold

Hints & Tips

Excess hardener will not significantly speed up the Gel. Time and could lead to bleed through and bleaching problems during over-painting



Black Filler





Technical Information

Part number:	85492	Mixing ratio	98:2
Description:	Black filler	Work time:	4-6 mins
Part code:	n/a	Sanding time:	20-30mins
Shelf life:	8 mths from manufacturing	Over coating:	1 hour
Selling Unit:	Ea	Service temp:	-20 to + 120°C
Hazard Info:	Harmful and oxidising		
Replacing:	n/a		
VOC;	150 G/L		
Customs Tariff code:	321410100		
MSDS:	yes		

Associated Products : Abrasives, Acrysol, Plastic Repair system (PRS), Quickfill, General filler range, Scuff Repair kit, Plastic prep, mixing pallet

VOC Markings :  2004/42/II(b)(250)150

Market Segments : Primary  Secondary 

Health & Safety Information



HARMFUL
contains styrene

Black Filler 85492 – (filler)

R10 FLAMMABLE
R20 Harmful by inhalation.
R36/38 Irritating to eyes and skin.
S3/7 Keep container tightly closed in a cool place.
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.
S37 Wear suitable gloves.
S38 In case of insufficient ventilation, wear suitable respiratory equipment.



IRRITANT
contains dibenzoyl peroxide



OXIDISING

Black Filler Hardener 84156 – (hardener)

R7 May cause fire.
R36 Irritating to eyes.
R43 May cause sensitization by skin contact.
S3/7 Keep container tightly closed in a cool place.
S37/39 Wear suitable gloves and eye/face protection.
S50 Do not mix with peroxide accelerators or reducing agents.
S62 If swallowed, do not induce vomiting: seek medical advice immediately and show this container or label.

In order to provide you with the most appropriate Personal Protective Equipment when using our products, KENT advises that you follow the guidelines on the packaging of the product before use. The guidelines are there for your protection and KENT provides a range of Personal Protection Equipment such as clothing, eye glasses, goggles, face shields and breathing apparatus, complying with the latest European legislation. If you require further advice then please phone our freephone number and we will be pleased to help you. Telephone: 0800 136925

Terms and Conditions

No part of this publication may be reproduced, transmitted or stored, electronically, mechanically or photocopied without the prior permission of KENT UK.

This data sheet and its contents (the "Information") belong to KENT UK or are licensed to it. No licence is granted for the use of it other than for information purposes in connection with the products to which it relates. No licence of any intellectual property rights is granted.

The Information is subject to change without notice and replaces all data sheets previously supplied. The Information supplied is believed to be accurate but the business assumes no responsibility for its accuracy or completeness, any error from or omission in it nor for any use made of it. Users of this data sheet should check for themselves the Information and the suitability of the products for their purpose and not make any assumptions based on information included or omitted. Liability for loss or damage resulting from any reliance on the Information or use of it (including

liability resulting from negligence or where the business was aware of the possibility of such loss or damage arising) is excluded. This will not operate to limit or restrict the business liability for death or personal injury resulting from its negligence.

Registered Office: 151 Longsight, Bolton, Lancashire BL2 3JE
Registered in England N°: 02519917
VAT Registration N°: 125 0226 61
All rights reserved.

KENT UK, Pitreavie Crescent, Pitreavie Business Park, Dunfermline, Fife KY11 8UQ
Tel : Freephone 0800 136925 or 01383 737393 between 08:30-17:30 Monday-Thursday, 09:00-15:00 on Fridays'. For out of hours queries please Fax us on 01383 735829 or
Email: KENTsales.UK@kenturope.com

DS375